



Dynalife™ GC-LB

Dynalife™ GC-LB is a high quality, multipurpose, extreme-pressure lithium complex grease developed to satisfy the severe lubrication requirements of heavily loaded plain and rolling element bearings operating at medium to high temperatures. It is NLGI GC-LB certified for use as a multipurpose automotive wheel bearing and chassis lubricant.

Dynalife™ GC-LB is manufactured with high quality paraffinic base oils thickened with lithium complex soap. It contains an effective extreme-pressure additive, a tackifier, and rust and oxidation inhibitors to provide excellent wear protection, excellent thermal stability at high temperatures, and excellent resistance to corrosion and water washout.

Dynalife™ GC-LB forms an effective seal to help minimize bearing contamination and provides a high level of adhesion to the bearing surface for improved retention, reduced leakage and resistance to water washout. It is dyed red for ease of identification.

Applications

- Wheel bearings of passenger cars, trucks, high performance vehicles, sport utility vehicles and motorcycles equipped with disc brakes
- Ball joints, universal joints, other chassis points, and water pumps on passenger cars, trucks, and other mobile equipment
- Centralized lube systems and auto lubbers in service shops

Outstanding Features

- Excellent high-temperature performance
- Excellent wear protection
- Good load-carrying ability (60-lb Timken OK Load rating)
- Excellent rust and corrosion inhibition
- Excellent resistance to water washout
- Good low-temperature pumpability
- NLGI GC-LB certified

**High Quality,
Extreme-Pressure
Automotive Lithium
Complex Grease;
NLGI GC-LB
Certified**

**U.S. Technical Services
Hot line:
1-800-766-0050**

**U.S. Customer Service:
1-800-822-6457**

**International:
+1-832-486-3363**

**E-mail address:
lubricants@
conocophillips.com**

<http://lubricants.conocophillips.com>

600 N. Dairy Ashford • 2W9000 • Houston, TX 77079



Dynalife™ GC-LB

Typical Properties

NLGI Grade	1	2
Thickener	Lithium Complex	Lithium Complex
Color	Red	Red
Dropping Point, °C (°F)	>260 (>500)	>260 (>500)
Density, lbs/gal	7.44	7.44
Penetration, ASTM D217 (worked 60 strokes)	325	280
Texture	Tacky	Tacky
Four-Ball EP, ASTM D2596, Weld Load, kgf	315	315
Four-Ball Wear, ASTM D2266, Scar Diameter, mm	0.37	0.50
Oxidation Stability, ASTM D942, 100 hours,		
Pressure Drop, psi (kPa)	5 (35)	5 (35)
Rust Prevention, ASTM D1743	Pass	Pass
Timken OK Load, ASTM D2509, lb	60	60
U.S. Steel Mobility, g/second		
@ 4°C (40°F)	4.74	2.61
@ -7°C (20°F)	1.49	0.94
@ -18°C (0°F)	0.20	0.10
Base Oil Properties,		
Viscosity,		
cSt @ 40°C	160	160
cSt @ 100°C	15.0	15.0
SUS @ 100°F	843	843
SUS @ 210°F	80	80
Viscosity Index	90	90
Usable Temperature Range,		
°C	-29 to 204	-23 to 204
°F	-20 to 400	-10 to 400

Due to continual product research and development, the information contained herein is subject to change without notification.

Copyright © ConocoPhillips Company. The ConocoPhillips logo, Conoco, the Conoco logo, Phillips 66, the Phillips 66 logo, 76 and the 76 logo are registered trademarks of ConocoPhillips Company in the U.S.A. and other countries.