



Versatrans™ ATF

Conoco VersaTrans™ Synthetic Blend ATF is a premium quality transmission fluid designed for use in automatic transmissions in most domestic and import passenger cars and light trucks. It has carefully balanced frictional properties for smooth shifting and excellent anti-shudder performance in a wide variety of vehicles. It has excellent shear stability and oxidation resistance for long service life, provides excellent wear protection, and helps protect against sludge and varnish buildup. The part-synthetic formulation provides better thermal stability at high temperatures and better low temperature properties than conventional all-mineral automatic transmission fluids.

VersaTrans™ Synthetic Blend ATF is fully approved for service fill in vehicles where a Ford MERCON®V, Ford MERCON®, GM DEXRON®-III, or Allison C-4 fluid is specified. It was designed and thoroughly field tested for many other applications, including Chrysler vehicles and most European and Japanese vehicles.

Applications

VersaTrans™ Synthetic Blend ATF is recommended for service fill in all domestic and import vehicles where DEXRON®-III, MERCON®V, or MERCON® fluids are specified. It also meets the performance requirements for Allison C-4, Caterpillar TO-2, Voith DIWA transmissions, and ZF Ecomat transmissions. It is recommended for use in most Chrysler, Acura, BMW, Honda, Hyundai, Jeep, Mercedes-Benz, Mitsubishi, Nissan, Saturn, Toyota, and VW vehicles. It also may be used in industrial and mobile hydraulic systems operating over a wide temperature range.

VersaTrans™ Synthetic Blend ATF is not recommended for vehicles with continuously variable transmissions (CVT), most 6-speed transmissions, or vehicles requiring a Ford Type F or MERCON® SP fluid.

VersaTrans™ Synthetic Blend ATF meets or exceeds the requirements of:

- Allison C-4
- Caterpillar TO-2 (obsolete)
- Chrysler ATF Specifications
- Denison HF-0

**Synthetic Blend
Multi-Vehicle
Automatic
Transmission Fluid**

**U.S. Technical
Services Hot line:
1-800-255-9556**

**U.S. Customer
Service:
1-800-640-1956**

**International:
+1-832-486-3363**

**Asia-Pacific:
tel: (65) 6536-0010
fax: (65) 6536-0012**

**E-mail address:
conocolubricants@
conocophilips.com**

www.lubes.conoco.com

600 N. Dairy Ashford • 2W9000 • Houston, TX 77079



- Ford MERCON®V, MERCON®
- GM DEXRON®-III (Approved for H Specification), DEXRON®-II
- Sundstrand Hydrostatic Transmissions
- Vickers M-2950-S and I-286-S
- Voith DIWA Transmissions
- ZF Ecomat Transmissions

Note: For questions about a specific application, please call our Technical Hotline.

Outstanding Features

- Optimum frictional properties for smooth shifting and excellent anti-shudder performance
- Outstanding thermal stability and oxidation resistance for long fluid life
- Outstanding low-temperature fluidity
- Excellent wear protection
- Minimizes sludge and varnish deposits
- Excellent rust and corrosion protection
- Good seal compatibility
- Thoroughly field tested in a wide range of automatic transmissions

VersaTrans™ ATF

Typical Properties

Density, g/cm ³ @ 15.6°C (60°F)	0.858
Color, Visual	Red
Flash Point (COC), °C (°F)	202 (396)
Pour Point, °C (°F)	-45 (-49)
Viscosity,	
cP @ -20°C (Brookfield)	900
cP @ -30°C (Brookfield)	2,600
cP @ -40°C (Brookfield)	8,600
cSt @ 40°C	35.0
cSt @ 100°C	7.4
SUS @ 100°F	177
SUS @ 210°F	50.9
Viscosity Index	185
Zinc, wt %	<0.002

Due to continual product research and development, the information contained herein is subject to change without notification.

© 2005 ConocoPhillips Company. Conoco logo is a trademark of ConocoPhillips Company or its subsidiaries.