



Brick Grease

Brick Grease is a hard, fibrous, sodium grease made in block or brick form. It is developed for the lubrication of open, low-speed, heavy-duty industrial bearings equipped with grease collars.

Brick Grease is manufactured with high quality base oils and sodium tallowate soap to provide exceptional protection for trunnion bearings.

Applications

- Kiln trunnion and support wall bearings
- Ball, tube, rod and mill bearings
- Paper machine dryer section bearings
- Kiln cars
- Dehydrators

Brick Grease can be used as is, or it can be cut into smaller blocks to fit the bearing opening. It normally rides directly on the bearing shaft. As the shaft rotates, it wipes a film of grease on the bearing surface, keeping it well lubricated over a wide temperature range.

Outstanding Features

- Compact 4½-pound brick for easy application
- Uniform consistency
- Provides good lubrication over wide range of bearing temperatures
- Does not harden, bake or glaze in service

High Quality, Non-EP Sodium Grease For Industrial Bearings

**U.S. Technical Services
Hot line:
1-800-766-0050**

**U.S. Customer Service:
1-800-822-6457**

**International:
+1-832-486-3363**

**E-mail address:
lubricants@
conocophillips.com**

<http://lubricants.conocophillips.com>

600 N. Dairy Ashford • 2W9000 • Houston, TX 77079



Brick Grease
Typical Properties

NLGI Grade	6
Thickener	Sodium
Color	Medium Amber
Dropping Point, °C (°F)	177 (350)
Density, lbs/gal	7.3
Penetration, ASTM D217 (unworked)	100
Texture	Fibrous
Base Oil Properties:	
Viscosity,	
cSt @ 40°C	100
cSt @ 100°C	12.8
SUS @ 100°F	517
SUS @ 210°F	71
Viscosity Index	123
Usable Temperature Range,	
°C	12 to 129
°F	+10 to 265

Due to continual product research and development, the information contained herein is subject to change without notification.

© 2005 ConocoPhillips Company. Phillips 66, Conoco and 76 logos are trademarks of ConocoPhillips Company or its subsidiaries.