



Cotton Picker

COTTON PICKER is a premium-quality lithium grease developed for the critical lubrication of cotton picker spindle heads located on the front of mechanical cotton pickers. These machines require lubricants that thoroughly protect the spindle heads as well as the rapidly rotating cotton plant strippers.

COTTON PICKER ensures complete lubrication and ease of starting of machinery during the fall harvest season, when temperatures begin to drop and ordinary greases sometimes fail to flow easily. It is semifluid and dyed green for ease of identification.

COTTON PICKER is manufactured with high-quality base oils and lithium 12-hydroxy stearate soap to provide exceptional protection for the spindle heads.

Applications

COTTON PICKER conforms to John Deere requirements and satisfactorily lubricates mechanical pickers requiring this type of grease.

Outstanding Features

- Protects spindles and bearings
- Eliminates spindles seizure or freeze-up
- Provides easy starting in cold weather
- Eliminates expensive downtime during harvest season
- Provides rust and corrosion inhibition to highly polished moving parts

**Premium Semifluid,
Non-EP Lithium
Grease For Cotton
Picker Spindles**

**U.S. Technical Services
Hot line:
1-800-766-0050**

**U.S. Customer Service:
1-800-822-6457**

**International:
+1-832-486-3363**

**E-mail address:
lubricants@
conocophillips.com**

<http://lubricants.conocophillips.com>

600 N. Dairy Ashford • 2W9000 • Houston, TX 77079

Cotton Picker
Typical Properties

ASTM Test Method		
NLGI Grade		00
Thickener		Lithium
Texture		Semifluid
Color		Dark Green
Density, lb/gal		7.38
Penetration (unworked)	D217	400-430
Dropping Point, °F (°C)	D2265	356 (180)
Oxidation Stability, Pressure Drop, psi (kpa)	D942	5 (35)
Four-Ball Wear, 75°C, mm	D2266	0.60
Base Oil Properties,		
cSt @ 40°C	D445	22.5
cSt @ 100°C	D445	4.2
SUS @ 100°F		118
SUS @ 210°F		40
Viscosity Index	D2270	65
Usable Temperature Range,		
°F		-15 to 256
°C		-26 to 124

Due to continual product research and development, the information contained herein is subject to change without notification.

© 2004 ConocoPhillips Company. Phillips 66, Conoco and 76 logos are registered trademarks of ConocoPhillips Company or its subsidiaries.