



Industrial Oil

Conoco Industrial Oil is a high-quality, general-purpose industrial lubricant formulated with paraffinic base stocks. Industrial Oil provides good thermal stability, low volatility and high purity.

Industrial Oil is available in nine different viscosity grades for use in a wide range of applications.

Applications

Seal oil, process oil, concrete form oil, deep-well pump drip oil, diluent, extender oil or other similar application.

Outstanding Features

- High purity
- Good thermal stability
- Low aromatics and low volatility
- Good lubricity
- Nonstaining

**General Purpose
Industrial And
Process Oil**

**U.S. Technical
Services Hot line:
1-800-255-9556**

**U.S. Customer
Service:
1-800-640-1956**

**International:
+1-832-486-3363**

**Asia-Pacific:
tel: (65) 6536-0010
fax: (65) 6536-0012**

**E-mail address:
*conocolubricants@
conocophillips.com***

www.lubes.conoco.com

600 N. Dairy Ashford • 2W9000 • Houston, TX 77079



**Industrial Oil
Typical Properties**

Grade	70	90	115	150	250	350	580	1200	2500
Viscosity,									
cSt @ 40°C	11	15	22	32	47	70	116	220	443
cSt @ 100°C	2.9	3.4	4.4	5.5	6.9	9.1	12.4	18.7	30.4
SUS @ 100°F	63	84	115	167	244	363	610	1164	2369
SUS @ 210°F	35	38	41	45	49	56	69	96	151
Viscosity Index	115	110	110	110	100	100	97	95	100
Pour Point,									
°F	-50	-5	5	5	5	5	10	10	5
°C	-46	-21	-15	-15	-15	-15	-12	-12	-15
Flash Point,									
°F	360	360	395	400	425	460	500	531	570
°C	182	182	202	204	218	238	260	277	299
ASTM Color	0.5	0.5	0.5	0.5	0.5	0.5	1.0	4.5	5.5
Density,									
lb/gal	7.09	7.09	7.11	7.16	7.20	7.23	7.29	7.40	7.48
g/ml	0.85	0.85	0.85	0.86	0.86	0.87	0.87	0.89	0.90
Carbon Residue (wt %)	0.06	0.06	0.06	0.06	0.06	0.06	0.06	0.18	0.24
Refractive Index	1.4487	1.4499	1.4517	1.4544	1.4569	1.4500	1.4600	1.4713	1.4742

Due to continual product research and development, the information contained herein is subject to change without notification.

© 2004 ConocoPhillips Company. Conoco and the Conoco logo are trademarks of ConocoPhillips Company or one of its subsidiaries.