



## PAG Gas Compressor Fluid XD2

PAG Gas Compressor Fluid XD2 is a full synthetic-based lubricant formulated for use in gas compression applications that require wide-operating temperature ranges, and minimum interaction between the lubricant and the process gas. It features higher-film strength than traditional lubricants, and it is fully compatible with most compressor components.

PAG Gas Compressor Fluid XD2 is available in one viscosity grade: ISO 68/100. It is formulated with synthetic base oils and carefully selected additives, which provide rust protection, oxidation resistance, corrosion inhibition and long service life.

### ***Applications***

- Oil-flooded rotary screw and rotary-vane compressors processing natural gas, carbon dioxide or other hydrocarbon gases

### ***Outstanding Features***

- Resists wash-off by hydrocarbon gases and liquids
- Resists absorption into the gas phase and carry-over of the lubricant downstream
- Insoluble in hydrocarbons, minimizes dilution effects
- Higher-film strength than traditional lubricants
- Protects against rust and corrosion
- Compatible with most compressor components including seals, gaskets and hoses

### ***Compatibility***

PAG Gas Compressor Fluid XD2 is compatible with the following solvents, elastomers and paints:

- Solvents: Acetone, Alcohol, Butyl Dioxol, Chlorinated Solvents, Glycol Ethers
- Elastomers: Neoprene, Silicone Rubber, Torlon, Vespal and Viton
- Paints: Epoxy

**Synthetic  
Polyglycol Rotary  
Compressor  
Lubricant For Gas  
Compression**

**U.S. Technical  
Services Hot Line:  
1-800-255-9556**

**U.S. Customer  
Service:  
1-800-640-1956**

**International:  
+1-832-486-3363**

**Asia-Pacific:  
tel: (65) 6536-0010  
fax: (65) 6356-0012**

**conocolubricants@  
conocophillips.com**

***www.lubes.conoco.com***

600 N. Dairy Ashford • 2W9000 • Houston, TX 77079



PAG Gas Compressor Fluid XD2 is not compatible with the following hydrocarbons and chemicals:

- Gasoline, Diesel Fuel, Kerosene, Heptane, Glycerol, Ethylene Glycol, Triethanolamine, Methanol and oil-based paints

**PAG Gas Compressor Fluid XD2**

**Typical Properties**

	<b>ASTM Method</b>	
<b>ISO Grade</b>		<b>68/100</b>
Gravity, °API	D287	5.88
Specific Gravity @ 60°F (15.6°C)		1.03
Density, lb/gal		8.59
Flash Point (COC), °F (°C)	D92	419 (215)
Fire Point (COC), °F (°C)	D92	455 (235)
Pour Point, °F (°C)	D97	-67 (-55)
Viscosity,	D445	
cSt @ 40°C		75.3
cSt @ 100°C		12.5
SUS @ 100°F		383
SUS @ 210°F		69
Viscosity Index	D2270	165
Total Acid Number (TAN)	D974	0.00
Copper Corrosion	D130	1b

Due to continual product research and development, the information contained herein is subject to change without notification.

© 2004 ConocoPhillips Company. Conoco logo is registered trademark of ConocoPhillips Company or its subsidiaries.