



Spindle Oil

Conoco Spindle Oil is a high-quality needle- and spindle-bearing lubricant formulated with hydrocracked base stocks and proprietary additive chemistry and oiliness agents.

Applications

Lubrication of high-speed needle and spindle bearings typically found in agriculture and textile equipment.

Machine tools and other equipment where a low-viscosity, thermally stable lubricant is required.

Spindle Oil is available in an ISO 15 viscosity grade.

Outstanding Features

- Excellent lubricity, oiliness and film strength
- Excellent low-temperature performance
- Nonstaining
- Good rust and corrosion protection
- Excellent thermal stability
- Good wear protection – long spindle life
- Good foam control

**High-Speed
Spindle Bearing
Lubricant**

**U.S. Technical
Services Hot line:
1-800-255-9556**

**U.S. Customer
Service:
1-800-640-1956**

**International:
+1-832-486-3363**

**Asia-Pacific:
tel: (65) 6536-0010
fax: (65) 6536-0012**

**E-mail address:
*conocolubricants@
conocophillips.com***

www.lubes.conoco.com

600 N. Dairy Ashford • 2W9000 • Houston, TX 77079



Spindle Oil
Typical Properties

ISO Grade	15
Viscosity,	
cSt @ 40°C	15
cSt @ 100°C	3.4
SUS @ 100°F	82
SUS @ 210°F	38
Viscosity Index	90
Pour Point,	
°F	-15
°C	-26
Flash Point,	
°F	370
°C	188
ASTM Color	0.0
Density,	
lb/gal	7.12
g/ml	0.85
Emulsion Characteristics (min. to 40-40-0)	10
Thermal Stability – Cincinnati Milacron (sludge, mg/100 ml)	1.1
Saponification Number	1.1

Due to continual product research and development, the information contained herein is subject to change without notification.

© 2004 ConocoPhillips Company. Conoco and the Conoco logo are trademarks of ConocoPhillips Company or one of its subsidiaries.