



## GT-1™ Diesel Motor Oil

Kendall GT-1™ Diesel Motor Oil is a premium quality, synthetic blend, API CI-4 motor oil specially designed for use in passenger car and light truck diesel engines. It is formulated to provide excellent wear protection, to minimize engine sludge and varnish deposits, and to resist viscosity and thermal breakdown even in severe service, such as towing and hauling under high temperatures. The part-synthetic formulation provides better oxidation resistance, reduced oil consumption and better low-temperature pumpability compared to conventional all-mineral motor oils.

### **Applications**

GT-1™ Diesel Motor Oil is recommended for use in passenger cars, vans, sport utility vehicles and light trucks with diesel engines. It meets the performance requirements of leading light-duty diesel engine manufacturers, including Cummins, International (Navistar), Isuzu and Mercedes-Benz.

GT-1™ Diesel Motor Oil meets or exceeds the requirements of:

- API Service CI-4, CH-4, CG-4, CF-4, CF, SL
- ACEA A3/B3
- Mercedes-Benz Sheet 229.1
- Dodge Cummins Diesel Engines
- Ford Powerstroke Diesel Engines
- GMC/Chevy Duramax Diesel Engines

### **Outstanding Features**

- Excellent resistance to viscosity and thermal breakdown at high temperatures
- Protects against engine sludge and varnish deposits
- Outstanding wear protection
- High TBN for extra protection in severe service intervals
- Excellent rust and bearing corrosion protection
- Outstanding low-temperature fluidity for easier cold-starts
- Low volatility for low evaporative losses and reduced oil consumption
- Good foam resistance

**Synthetic Blend  
Motor Oil For Light-  
Duty Diesel Engines**

**Customer Service  
Number:  
1-800-368-7128**

**Technical  
Hot line:  
1-800-368-1267**

**E-mail address:  
*kendallmotoroil@  
conocophillips.com***

***[www.kendallmotoroil.com](http://www.kendallmotoroil.com)***

**600 N. Dairy Ashford • 2W9000 • Houston, TX 77079**

---

**GT-1™ Diesel Motor Oil**  
**Typical Properties**

---

<b>SAE GRADE</b>	<b>15W-40</b>
Density, g/cm <sup>3</sup> @ 15.6°C (60°F)	0.876
Pounds per U.S. Gallon @ 15.6°C (60°F)	7.28
Color, ASTM D1500	L 4.0
Flash Point (COC), °C (°F)	230 (446)
Pour Point, °C (°F)	-36 (-33)
Viscosity,	
cSt @ 40°C	116
cSt @ 100°C	15.3
SUS @ 100°F	598
SUS @ 210°F	80.8
Viscosity Index	139
Cold Cranking Viscosity, cP @ -20°C	5,850
High Temp/High Shear Viscosity, cP @ 150°C	4.3
Sulfated Ash, ASTM D874, wt %	1.3
Total Base Number (TBN), ASTM D2896	10.8
Zinc, wt %	0.134

---

Due to continual product research and development, the information contained herein is subject to change without notification.

---

© 2005 ConocoPhillips Company. Kendall and the Kendall logo are trademarks of ConocoPhillips Company or its subsidiaries.