



## **Conoco HD Fleet™ Engine Oil**

Conoco HD Fleet™ Engine Oil is formulated from superior-quality, paraffinic base oils and high-performance additives to provide excellent wear protection and soot control in 2-stroke cycle diesel engines. Conoco HD Fleet™ Engine Oil meets the requirements of the Caterpillar TO-2 specification and also is recommended for applications requiring Allison Type C-4 approval. The SAE 30, 40 and 50 grades meet API CF-2 and are recommended for Detroit Diesel 2-cycle engine service.

Conoco HD Fleet™ Engine Oils meet the following Industry and OEM Specifications:

- API CF/CF-2 (SAE 30, 40 and 50)
- Caterpillar TO-2
- Allison C-4
- Detroit Diesel 7SE 270

### ***Outstanding Features***

- Controls soot, deposits and wear
- Protects against rust and corrosion
- Resists oxidation and foaming
- Excellent Dispersancy and TBN retention in service

**Low Ash Engine  
Oil For 2-Stroke  
Cycle Diesel  
Engine**

**U.S. Technical  
Services Hot line:  
1-800-255-9556**

**U.S. Customer  
Service:  
1-800-640-1956**

**International:  
+1-832-486-3363**

**Asia-Pacific:  
tel: (65) 6536-0010  
fax: (65) 6536-0012**

**E-mail address:  
*conocolubricants@  
conocophilips.com***

***www.lubes.conoco.com***

**600 N. Dairy Ashford • 2W9000 • Houston, TX 77079**



**Conoco HD Fleet™ Engine Oil**  
**Typical Properties**

<b>SAE Grade</b>	<b>10W</b>	<b>20W-20</b>	<b>30</b>	<b>40</b>	<b>50</b>
API Service CF-2	n/a	n/a	X	X	X
API Service CF	X	X	X	X	X
Detroit Diesel 7SE 270	n/a	n/a	X	X	X
Caterpillar T0-2	X	X	X	X	X
Allison C-4	(1)	n/a	(1)	n/a	n/a
MIL-CID-A-A-52306, SAE J2363	n/a	n/a	(1)	(1)	n/a

X – Meets or exceeds specification  
 (1) – Recommended for application requiring this specification  
 n/a – not applicable

**Conoco HD Fleet™ Engine Oil**  
**Typical Properties**

<b>Product</b>	<b>Density</b>	<b>Pour °C (°F)</b>	<b>Flash °C (°F)</b>	<b>cSt at 40°C</b>	<b>cSt at 100°C</b>	<b>% SASH</b>	<b>Color ASTM</b>	<b>TBN</b>	<b>V.I.</b>
Conoco HD Fleet 10W	0.872	-39(-39)	198 (390)	48	7.5	0.94	L2.5	7.5	122
Conoco HD Fleet 20W-20	0.875	-36 (-33)	207 (405)	72	8.5	0.94	4.0	7.5	116
Conoco HD Fleet 30	0.879	-33 (-27)	208 (410)	88	11.0	1.0	L4.0	8.1	109
Conoco HD Fleet 40	0.882	-27 (-17)	208 (410)	149	15.4	1.0	4.0	8.1	106
Conoco HD Fleet 50	0.887	-27 (-17)	207 (410)	207	20	1.0	4.0	8.1	104

Due to continual product research and development, the information contained herein is subject to change without notification.

© 2004 ConocoPhillips Company. Conoco and the Conoco logo are trademarks of ConocoPhillips Company or one of its subsidiaries.

