



Conoco HD Fleet Supreme™ Engine Oil

Conoco HD Fleet Supreme™ Engine Oil is a high-quality, universal fleet engine oil formulated from premium base stocks and special additive technology. It satisfies the warranty requirements of most domestic and foreign diesel engine manufacturers. Conoco HD Fleet Supreme™ Engine Oil meets or exceeds the latest requirements of API CI-4 Plus service, Mack EO-N Premium Plus 03, EO-M Plus, EO-M, Cummins CES 20071, 20076, and 20078 and Volvo VDS-2/VDS specifications. It is specifically formulated to meet the needs of modern heavy-duty diesel engines equipped with EGR (Exhaust Gas Recirculation) or other technologies for emissions control. Conoco HD Fleet Supreme™ Engine Oil meets Caterpillar specification ECF-1 and is recommended for use in all Caterpillar engines, including the new ACERT engines. Conoco HD Fleet Supreme™ Engine Oil also is recommended for older engines requiring all previous API "C" categories of oil performance.

Conoco HD Fleet Supreme™ Engine Oil is recommended for off-road applications in engines manufactured by Cummins, Detroit Diesel, MTU, Caterpillar, Mack, Navistar, John Deere, Komatsu, Scania, Volvo and others. It is technologically advanced to provide excellent soot control, as well as protect against wear, deposits, rust and corrosion, foaming, and high-temperature oil oxidation and thickening.

Outstanding Features

- Excellent performance in modern diesel engines utilizing cooled EGR for emission control
- Excellent performance in older-generation diesel engines operating both on-road and off-road
- Superior soot handling and wear control
- Effective stay in grade performance
- Protects against rust and corrosion

**A High-Quality,
Universal Fleet
Engine Oil**

**U.S. Technical
Services Hot line:
1-800-255-9556**

**U.S. Customer
Service:
1-800-640-1956**

**International:
+1-832-486-3363**

**Asia-Pacific:
tel: (65) 6536-0010
fax: (65) 6536-0012**

**E-mail address:
*conocolubricants@
conocophilips.com***

www.lubes.conoco.com

600 N. Dairy Ashford • 2W9000 • Houston, TX 77079



Conoco HD Fleet Supreme™ Engine Oil
Typical Properties

SAE Grade	15W-40	10W-30
API Diesel Service CI-4 Plus	X	n/a
API Diesel Service CI-4, CH-4, CG-4, CF-4, CF	X	X
API Gasoline Service SL, SH	X	X
API Gasoline Service SJ	X	X
Mack EO-N Premium Plus 2003	X	n/a
Mack EO-M Plus, EO-M	X	X
Mack EO-L Plus, EO-L	X	X
Volvo VDS-2/VDS	X	n/a
Caterpillar ECF-1	X	X
Cummins CES 20078	X	n/a
Cummins CES 20076, 20072, 20071	X	X
Navistar TSI-02-12-20	X	X
Detroit Diesel 7SE 270	X	X
MTU, Type 1	X	X
Caterpillar T0-2	(1)	(1)
Allison C-4	(1)	(1)
Ford WSS-M2C171-D	(1)	(1)

X – Meets or exceeds specification

(1) – Recommended for application requiring this specification

n/a – not applicable

Conoco HD Fleet Supreme™
Typical Properties

Product	Density	Pour °C (°F)	Flash °C (° F)	cSt at 40° C	cSt at 100° C	% SASH	Color ASTM	TBN	V.I.
Conoco HD Fleet Supreme 15W-40	0.880	-39 (-38)	190 (400)	115	15.2	1.2	L4.0	9.5	137
Conoco HD Fleet Supreme 10W-30	0.871	-39 (-39)	185 (390)	79.4	12.0	1.2	L4.0	9.3	143

Due to continual product research and development, the information contained herein is subject to change without notification.

© 2004 ConocoPhillips Company. Conoco and the Conoco logo are trademarks of ConocoPhillips Company or one of its subsidiaries.

