



Non-Detergent Motor Oil

Kendall Non-Detergent Motor Oil is a high-quality non-detergent motor oil recommended for use in all applications that specify a non-detergent oil. It is formulated to provide good wear protection and resistance to oxidation, rust and corrosion, and foaming. It meets API Service SB performance requirements.

Applications

Non-Detergent Motor Oil is recommended for use in certain air compressors and other industrial applications that require a non-detergent, non-EP oil. The SAE 30 viscosity grade also is suitable for use in gasoline engines operated under such mild conditions that the protection provided by compounded oils is not required.

Non-Detergent Motor Oil is **not** recommended for use in automotive gasoline engines built after 1963.

Non-Detergent Motor Oil meets the requirements of:

- API Service SB

Outstanding Features

- Good oxidation resistance
- Good wear protection
- Good rust and corrosion protection
- Good foam resistance

**Non-Detergent API
SB Motor Oil**

**Customer Service
Number:
1-800-368-7128**

**Technical
Hot line:
1-800-368-1267**

**E-mail address:
*kendallmotoroil@
conocophillips.com***

www.kendallmotoroil.com

600 N. Dairy Ashford • 2W9000 • Houston, TX 77079

Non-Detergent Motor Oil
Typical Properties

SAE GRADE	10W	20W-20	30
Density, g/cm ³ @ 15.6°C (60°F)	0.862	0.875	0.871
Pounds per U.S. Gallon @ 15.6°C (60°F)	7.18	7.29	7.25
Color, ASTM D1500	3.0	3.0	3.0
Flash Point (COC), °C (°F)	240 (464)	235 (455)	240 (464)
Pour Point, °C (°F)	-15 (5)	-15 (5)	-15 (5)
Viscosity,			
cSt @ 40°C	32	46	92
cSt @ 100°C	5.5	7.0	11.0
SUS @ 100°F	165	237	478
SUS @ 210°F	44.7	49.7	63.9
Viscosity Index	104	104	104
Sulfated Ash, ASTM D874, wt %	0.2	0.2	0.2
Zinc, wt %	0.06	0.06	0.06

Due to continual product research and development, the information contained herein is subject to change without notification.

© 2005 ConocoPhillips Company. Kendall and the Kendall logo are trademarks of ConocoPhillips Company or one of its subsidiaries.