



Super ATF

Super ATF is a high-quality transmission fluid recommended for use in most GM and many Ford automatic transmissions in 2005 and earlier model-year vehicles that are no longer under warranty.

Super ATF is formulated to provide the proper frictional characteristics for smooth, quiet shifting in electronically controlled automatic transmissions. It has excellent oxidation resistance for long fluid life, excellent low-temperature properties, protects against wear and helps minimize the formation of sludge and varnish.

Applications

Super ATF is recommended for service fill in GM and Ford automatic transmissions in 2005 and earlier model-year vehicles that are no longer under warranty and do **not** require a MERCON®SP, MERCON®V, Type F or Type T-IV fluid. It also is recommended for use in import vehicles where the automaker specifies the same transmission fluid as used in GM vehicles for 2005 and earlier model-years. It also meets the performance requirements of Allison C-4.

Super ATF may be used in industrial and mobile hydraulic systems operating over a wide temperature range.

Super ATF is **not** recommended for use in automatic transmissions that require a GM DEXRON®-VI or Ford MERCON®V fluid for warranty coverage, or in continuously variable transmissions (CVTs).

Features/Benefits

- Proper frictional properties for smooth shifting and excellent anti-shudder performance
- Excellent thermal stability and oxidation resistance for long fluid life
- Excellent low-temperature properties
- Protects against wear
- Minimizes sludge and varnish deposits
- Protects against rust and corrosion
- Good seal compatibility
- Suitable for both automotive and industrial applications

**Transmission Fluid
For Older GM And
Ford Automatic
Transmissions**

Contact Information

**U.S. Customer
Service:
1-800-822-6457**

**Technical Hot Line:
1-800-766-0050**

**International
Customer Service:
+1-832-486-3363
+1-832-486-3870**

**E-mail address:
lubricants@
conocophillips.com**

<http://lubricants.conocophillips.com>

600 N. Dairy Ashford • 2W9000 • Houston, TX 77079



Super ATF

Typical Properties

Specific Gravity @ 60°F	0.862
Density, lbs/gal @ 60°F	7.19
Color, Visual	Red
Flash Point (COC), °C (°F)	206 (403)
Pour Point, °C (°F)	-57 (-71)
Viscosity, Brookfield	
cP @ -40°C	17,000
Viscosity, Kinematic	
cSt @ 40°C	35.4
cSt @ 100°C	7.6
Viscosity Index	193
Zinc, wt %	<0.003

Health and Safety Information

For recommendations on safe handling and use of this product, please refer to the Material Safety Data Sheet via <http://w3.conocophillips.com/NetMSDS>.

Typical properties are average values only and do not constitute a specification. Minor variations that do not affect product performance are to be expected during normal manufacture, and at different blending locations. Product formulations are subject to change without notification.

Copyright © 2009 ConocoPhillips Company. The ConocoPhillips logo, Conoco, the Conoco logo, Phillips 66, the Phillips 66 logo, 76 and the 76 logo are trademarks of ConocoPhillips Company in the U.S.A. and other countries.

